


# GSESLC3V3D3020-10U Ultra Low Capacitance ESD TVS Array


## Features

- Transient protection for high-speed data lines  
IEC 61000-4-2 (ESD)  $\pm 30\text{kV}$  (Air)  
 $\pm 30\text{kV}$  (Contact)  
IEC 61000-4-4 (EFT) 40A (5/50 ns) IEC  
61000-4-5 (Surge) 40A (8/20 $\mu\text{s}$ )
- Package optimized for high-speed lines
- Provides protection for two line pairs
- Low capacitance: 3.75pF @ 0V (MAX)
- Low leakage current: 0.1 $\mu\text{A}$  @ VRWM (Typical)
- Low operating and clamping voltage
- Each I/O pin can withstand over 1000 ESD strikes for  $\pm 8\text{kV}$  contact discharge



## Applications

- 10/100/1000M Ethernet Ports
- WAN/LAN Equipment
- Desktops, Servers and Notebooks
- Cellular Phones
- Switching Systems
- Audio/Video Inputs



Schematic Diagram

## Absolute Maximum Ratings ( $T_A=25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Value	Units
IEC 61000-4-2 ESD Voltage	Air Model	$\pm 30$	kV
	Contact Model	$\pm 30$	
Peak Pulse Power ( $t_p = 8/20\mu\text{s}$ )	$P_{PP}$	1000	W
Peak Pulse Current	$I_{PP}$	40	A
Operating Temperature	$T_{OPT}$	-55 to +125	$^\circ\text{C}$
Storage Temperature	$T_{STG}$	-55 to +150	

# GSESLC3V3D3020-10U

## Ultra Low Capacitance ESD TVS Array

### Electrical Parameter (T=25°C)

Symbol	Parameter
$V_{RWM}$	Nominal Reverse Working Voltage
$I_R$	Reverse Leakage Current @ $V_{RWM}$
$V_{t1}$	Trigger Voltage
$I_{t1}$	Trigger Current @ $V_{t1}$
$V_h$	Holding Voltage
$I_h$	Holding Current @ $V_h$
$V_C$	Clamping Voltage @ $I_{PP}$
$I_{PP}$	Maximum Peak Pulse Current
$C_{ESD}$	Parasitic Capacitance




### Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise specified)


Symbol	Test Condition	Minimum	Typical	Maximum	Units
$V_{RWM}$	-	-	-	3.3	V
$I_R$	$V_{RWM} = 3.3V$	-	5	500	nA
$I_R$	$V_{RWM} = 3.3V, T_a=100^\circ C$	-	20	-	nA
$V_{t1}$	$I_{t1} = 1\mu A$	3.8	4.5	5.5	V
$V_h$	$I_h = 1mA$	3.5	-	5.5	V
$V_C$	Any I/O to Ground $I_{PP} = 1A, t_p = 8/20\mu s$	-	-	5.5	V
$V_C$	Any I/O to Ground $I_{PP} = 10A, t_p = 8/20\mu s$	-	-	10.5	V
$V_C$	Any I/O to Ground $I_{PP} = 25A, t_p = 8/20\mu s$	-	-	18.0	V
$V_C$	Line-to-Line / Line-to-GND, two I/O Pins connected together on each line $I_{PP} = 40A, t_p = 8/20\mu s$	-	-	25.0	V
$C_{ESD}$	Between I/O Pins and Ground $V_R = 0V, f = 1MHz$	-	3.8	5.0	pF
$C_{ESD}$	Between I/O Pins $V_R = 0V, f = 1MHz$	-	1.7	2.5	pF

**Typical Characteristic Curve**


**Clamping Voltage  $V_C$  vs. Current  $I_{PP}$**   
 Any I/O to GND




**Clamping Voltage  $V_C$  vs. Current  $I_{PP}$**   
 Line-to-Line, Two I/O Pins Connected Together




**Insertion Loss S21**




**Normalized Capacitance vs. Voltage**



**ESD Clamping of I/O to GND**  
 (+8kV Contact per IEC 61000-4-2)



**ESD Clamping of I/O to GND**  
 (-8kV Contact per IEC 61000-4-2)




# **GSESLC3V3D3020-10U**

## **Ultra Low Capacitance ESD TVS Array**

### **Application Information**

Electronic equipment is susceptible to damage caused by a variety of sources, including Electrostatic Discharge (ESD), Electrical Fast Transients (EFT) and Lightning strikes. The GSESLC3V3D3020-10U was designed to protect the sensitive equipment from damage which may be induced by such transient events. This product can be configured in different connections to meet the requirement of common-mode and differential-mode as follows:

### **Gigabit Ethernet Protection**




NOTE: Please connect pin3, Pin8 and all GND Tabs of GSESLC3V3D3020-10U to the ground plane of the systems.

# GSESLC3V3D3020-10U

## Ultra Low Capacitance ESD TVS Array

### Package Outline Dimensions



Symbol	Dimensions (mm)			Dimensions (Inches)		
	Minimum	Typical	Maximum	Minimum	Typical	Maximum
A	0.500	0.600	0.650	0.020	0.024	0.026
A1	0.000	0.030	0.050	0.000	0.001	0.002
A3	0.15 REF			0.006 REF		
b	0.150	0.200	0.250	0.006	0.008	0.010
b1	0.250	0.350	0.450	0.010	0.014	0.018
D	2.900	3.000	3.100	0.114	0.118	0.122
E	1.900	2.000	2.100	0.075	0.079	0.083
e	0.600 BSC			0.024 BSC		
e1	0.650 BSC			0.026 BSC		
e2	0.950 BSC			0.037		
L	0.250	0.300	0.350	0.010	0.012	0.014
L1	0.950	1.000	1.050	0.037	0.039	0.041