


Features


- High collector current
- Complementary to BC807
- SOT-23 plastic package

Applications

- Switching application
- General power amplifier



SOT-23



Schematic Diagram

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	50	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current-Continuous	I_C	500	mA
Collector Current-Peak Collector Current	I_{CM}	1.0	A
Collector Power Dissipation	P_C	300	mW
Thermal Resistance From Junction to Ambient	$R_{\theta JA}$	417	$^{\circ}\text{C}/\text{W}$
Junction Temperature Range	T_J	-55 to +150	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}\text{C}$

Classification Of $h_{FE(1)}$ Marking Information

h_{FE} Classification	GSBC817	GSBC817-16	GSBC817-25	GSBC817-40
h_{FE} Range	100 to 600	100 to 250	160 to 400	250 to 600
Marking	6D	6A	6B	6C

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CB0}	$I_C=10\mu\text{A}, I_E=0$	50	-	-	V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=10\text{mA}, I_B=0$	45	-	-	V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E=10\mu\text{A}, I_C=0$	5.0	-	-	V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=45\text{V}, I_E=0$	-	-	100	nA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=4\text{V}, I_C=0$	-	-	100	nA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=1.0\text{V}, I_C=100\text{mA}$	100	-	600	-
	$h_{FE(2)}$	$V_{CE}=1.0\text{V}, I_C=500\text{mA}$	40	-	-	-
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=500\text{mA}, I_B=50\text{mA}$	-	-	0.7	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=500\text{mA}, I_B=50\text{mA}$	-	-	1.2	V
Base to Emitter Voltage	V_{BE}	$V_{CE}=1.0\text{V}, I_C=500\text{mA}$	-	-	1.2	V
Transition Frequency	f_T	$V_{CE}=5.0\text{V}, I_C=10\text{mA}$ $F=100\text{MHz}$	100	-	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0, F=1.0\text{MHz}$	-	5.0	-	pF

Typical Characteristic Curves




Figure 1. Static Characteristics




Figure 2. DC Current Gain vs. Collector Current




Figure 3. Base-Emitter Saturation Voltage vs. Collector Current




Figure 4. Collector-Emitter Saturation Voltage vs. Collector Current




Figure 5. Collector Current vs. Base-Emitter Voltage




Figure 6. Capacitance Characteristics

Typical Characteristic Curves




Figure 7. Transition Frequency vs. Collector Current






Figure 8. Power Dissipation vs. Ambient Temperature

Package Outline Dimensions (SOT-23)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.510	0.012	0.020
c	0.080	0.180	0.003	0.007
D	2.800	3.040	0.110	0.120
E	1.200	1.400	0.047	0.055
E1	2.100	2.640	0.083	0.104
e	0.890	1.030	0.035	0.041
e1	1.780	2.050	0.070	0.081
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.018
θ	0°	8°	0°	8°

Recommended Pad Layout



Note:

1. Controlling dimension: in millimeters
2. General tolerance: $\pm 0.05\text{mm}$
3. The pad layout is for reference purposes only

Order Information

Device	Package	Carrier	Quantity
GSBC817 Series	SOT-23	Tape & Reel	3,000 Pcs / Reel

For more information, please contact us at: inquiry@goodarksemi.com