



Features

- Epoxy meets UL-94V-0 flammability rating
- Power dissipation of 300mW
- High stability and high reliability



SOT-23




Schematic Diagram

Mechanical Data

- Case:SOT-23
- Terminals: Plated solderable per MIL-STD-750, method 2026
- Mounting position: Any

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---|-----------------|-------------|-----------------------------|
| Collector-Emitter Voltage | V_{CEO} | -25 | V |
| Collector-Base Voltage | V_{CBO} | -40 | V |
| Emitter-Base Voltage | V_{EBO} | -5 | V |
| Collector Current, Continuous | I_C | -1500 | mA |
| Collector Power Dissipation | P_D | 300 | mW |
| Thermal Resistance from Junction to Ambient | $R_{\theta JA}$ | 417 | $^{\circ}\text{C}/\text{W}$ |
| Operation Junction Temperature | T_J | -55 to +150 | $^{\circ}\text{C}$ |
| Storage Temperature | T_{STG} | -55 to +150 | $^{\circ}\text{C}$ |



Electrical Characteristics (T_A=25°C unless otherwise noted)

| Parameter | Symbol | Conditions | Min | Max | Unit |
|--------------------------------------|----------------------|---|------|-------|------|
| Collector-Emitter Breakdown Voltage | V _{(BR)CEO} | I _C =-0.1mA, I _B =0 | -25 | - | V |
| Collector-Base Breakdown Voltage | V _{(BR)CBO} | I _C =-100μA, I _E =0 | -40 | - | V |
| Emitter-Base Breakdown Voltage | V _{(BR)EBO} | I _E =-100μA, I _C =0 | -5.0 | - | V |
| Collector Cut-Off Current | I _{CBO} | V _{CB} =-40V, I _E =0 | - | -100 | nA |
| Collector Cut-Off Current | I _{CEO} | V _{CE} =-20V, I _B =0 | - | -100 | nA |
| Emitter Cut-Off Current | I _{EBO} | V _{EB} =-5V, I _C =0 | - | -100 | nA |
| Current Gain | h _{FE} | I _C =5mA, V _{CE} =-1V | - | - | - |
| | h _{FE(1)} | I _C =-100mA, V _{CE} =-1V | 200 | 350 | |
| | h _{FE(2)} | I _C =-800mA, V _{CE} =-1V | 40 | - | |
| Collector-Emitter Saturation Voltage | V _{CE(sat)} | I _C =10mA, I _B =1.0mA | - | - | V |
| | | I _C =-800mA, I _B =-80mA | - | -0.5 | |
| Base-Emitter Saturation Voltage | V _{BE} | I _C =-800mA, I _B =-80mA | - | -1.20 | V |
| | | V _{CE} =-1V, I _C =-10mA | - | - | |
| Output Capacitance | C _{ob} | V _{CB} =-10V, F=1.0MHZ, I _E =0 | - | 20 | pF |
| Input Capacitance | C _{ib} | V _{EB} =0.5V, F=1.0MHZ, I _C =0 | - | - | pF |
| Current Gain-Bandwidth Product | f _T | I _C =-50mA, V _{CE} =-10V, F=30MHZ | 100 | - | MHZ |
| Noise Figure | N _F | V _{CE} =5.0V, F=1.0KHZ, I _C =100μA, R _S =1.0K | - | - | dB |

Typical Characteristic Curves




Figure 1. Static Characteristic




Figure 2. DC Current Gain vs. Collector Current




Figure 3. Base-Emitter Saturation Voltage vs. Collector Current




Figure 4. Collector-Emitter Saturation Voltage vs. Collector Current




Figure 5. Collector Current vs. Base-Emitter Voltage




Figure 6. Capacitance Characteristics

Typical Characteristic Curves




Figure 7. Transition Frequency vs. Collector Current






Figure 8. Power Dissipation vs. Ambient Temperature

Package Outline Dimensions (SOT-23)



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|------|----------------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 2.70 | 3.10 | 0.106 | 0.122 |
| B | 0.35 | 0.50 | 0.014 | 0.020 |
| C | 2.20 | 3.00 | 0.087 | 0.118 |
| D | 1.20 | 1.65 | 0.047 | 0.065 |
| E | 0.89 | 1.02 | 0.035 | 0.040 |
| F | 1.78 | 2.04 | 0.070 | 0.080 |
| G | 0.08 | 0.19 | 0.003 | 0.007 |
| H | 0.90 | 1.40 | 0.035 | 0.055 |
| I | 0.10 REF | | 0.004 REF | |

Recommended Pad Layout



Order Information

| Device | Package | Marking | Packaging | SPQ |
|---------|---------|---------|-------------|-----------------|
| GSS8550 | SOT-23 | Y2 | Tape & Reel | 3,000pcs / Reel |

For more information, please contact us at: inquiry@goodarksemi.com