


Features

- Low equivalent on-resistance



Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)







Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CB0}	80	V
Collector-Emitter Voltage	V_{CEO}	60	V
Emitter-Base Voltage	V_{EBO}	5	V
Collector Current	I_C	1	A
Peak Pulse Current	I_{CM}	2	A
Collector Power Dissipation	P_C	250	mW
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	500	$^{\circ}\text{C}/\text{W}$
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to+150	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)



Parameter	Symbol	Test Conditions	Min	Max	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	80	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	60	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=100\mu\text{A}, I_C=0$	5	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB}=60\text{V}, I_E=0$	-	0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=4\text{V}, I_C=0$	-	0.1	μA
DC Current Gain	$h_{FE(1)}^*$	$V_{CE}=5\text{V}, I_C=1\text{mA}$	100	-	
	$h_{FE(2)}^*$	$V_{CE}=5\text{V}, I_C=500\text{mA}$	100	300	
	$h_{FE(3)}^*$	$V_{CE}=5\text{V}, I_C=1\text{A}$	80	-	
	$h_{FE(4)}^*$	$V_{CE}=5\text{V}, I_C=2\text{A}$	30	-	
Collector-Emitter Saturation Voltage	$V_{CE(sat)1}^*$	$I_C=500\text{mA}, I_B=50\text{mA}$	-	0.25	V
	$V_{CE(sat)2}^*$	$I_C=1\text{A}, I_B=100\text{mA}$	-	0.5	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}^*$	$I_C=1\text{A}, I_B=100\text{mA}$	-	1.1	V
Base-Emitter Voltage	V_{BE}^*	$V_{CE}=5\text{V}, I_C=1\text{A}$	-	1	V
Transition Frequency	f_T	$V_{CE}=10\text{V}, I_C=50\text{mA}, f=100\text{MHz}$	150	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$	-	10	pF

*Pulse test: pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2.0\%$.


Typical Characteristic Curves



Typical Characteristic Curves




Package Outline Dimensions SOT-23



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0 $^\circ$	8 $^\circ$	0 $^\circ$	8 $^\circ$

Suggested Pad Layout



Note:
1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Marking and Ordering Information

Device	Package	Marking	Quantity	HSF Status
MMBT491	SOT-23	491	3,000pcs / Reel	RoHS Compliant